



HSB-100WC 英制垫片规格及公差

HSB-100WC Inch Thrust Washer Specification & Tolerance



尺寸：英寸
All dimensions in inch



垫片型号标注方式

Washer Symbol

垫片型号标注方式 Washer Symbol	HDU - □	WC	× ×
垫片型号 Washer Type			
垫片 Washer			
垫片内径 Washer I.D.			

单位Unit: Inch

型号 Part No	内径 Internal Diameter d		外径 External Diameter D		壁厚 Thickness s	定位孔中心 Dowel Hole PCD- Φ H _m ± 0.12	定位孔直径 Dowel Hole- Φ H	Recess Depth H _a
	min.	max.	min.	max.				
HDU WC 06	0.510	0.500	0.865	0.875	0.063 0.061	0.077 0.067	0.6870	0.050 0.040
HDU WC 07	0.572	0.562	0.990	1.000			0.7810	
HDU WC 08	0.635	0.625	1.115	1.125		0.109 0.099	0.8750	
HDU WC 09	0.697	0.687	1.177	1.187			0.9370	
HDU WC 10	0.760	0.750	1.240	1.250			1.0000	
HDU WC 11	0.822	0.812	1.365	1.375			1.0940	
HDU WC 12	0.885	0.875	1.490	1.500		0.140 0.130	1.1870	
HDU WC 14	1.010	1.000	1.740	1.750			1.3750	
HDU WC 16	1.135	1.125	1.990	2.000		0.171 0.161	1.5620	
HDU WC 18	1.260	1.250	2.115	2.125			1.6870	
HDU WC 20	1.385	1.375	2.240	2.250			1.8020	
HDU WC 22	1.510	1.500	2.490	2.500		0.202 0.192	2.0000	
HDU WC 24	1.635	1.625	2.615	2.625			2.1250	
HDU WC 26	1.760	1.750	2.740	2.750			2.2500	
HDU WC 28	2.010	2.000	2.990	3.000	0.093 0.091		2.5000	
HDU WC 30	2.135	2.125	3.115	3.125			2.6250	
HDU WC 32	2.260	2.250	3.240	3.250			2.7500	